

# EXPLORER 7120

1.2 Meter Auto-Deploy, Drive-Away Antenna System

# COBHAM

September 2014 Product Sheet

The most important thing we build is trust



## EXPLORER 7120

The EXPLORER 7120 is a 1.2m Ku-band drive-away antenna. Its low stow height and lightweight positioner make it for easy installation on a variety of smaller vehicles including SUVs and vans. This auto-deploy system allows personnel with minimal satellite experience to easily configure and operate this terminal enabling the user to access any broadband application over satellite.

### System Features

- Rugged, Reliable 1.2m Ku-band Drive-Away Antenna
- Low stow height of 38 cm (15")
- Solid Resin Fiber Composite Reflector: High EIRP, High-Performance
- Mechanical Drive systems including Zero-Backlash Az/El Cable Drive, and Precision Polarization Drive
- WR-75 Flex WaveGuide to BUC interface
- Inclined orbit satellite tracking
- Manual override capability for emergency use

### Applications

- Continuity of Business Operations
- Remote Business Videoconferencing
- Internet Cloud Services: Voice, Radio, Data, Fax, Live Broadcast

### Markets

- Military
- Homeland Security
- Emergency Response
- Law Enforcement
- Media: Live Streaming Video, TV Broadcasting
- Telemedicine: Critical Medical Information Transmission
- Mobile Insurance Claims & Settlements
- Remote Office Communications
- Energy and Mining

### Reflector

Size	1.2m Single-Piece Resin Fiber Composite
Optics	Offset, Prime Focus, 0.8 F/D
Mount Geometry	3-Axis, Elevation over Azimuth
Polarization	Motorized Rotation of Feed

### Mechanical

Positioner	Cable Drive
BUC/HPA Mounting	Feed Boom -maximum weight 6.7 kg (15 lbs) Maximum BUC mounting dimensions: 56 L x 35 W x 22 H cm (22" L x 13.8" W x 8.5" H)
Travel Velocity Azimuth	400° or ± 200°
Elevation	0-90° antenna boresight (mechanical) Standard limits at 5° to 65° (CE Approval) or 5° to 90° (operational)
Polarization	±95°
Slewing & Deploying	2° per second
Manual Jog	1.0° or 0.2° per second

### Weights & Measures

Approx. Weight	46 to 55 kg (100 to 120 lbs.) depending on options
Stowed Dimensions	178 L x 122 W x 38 H cm (70" L x 48" W x 15" H)
Antenna Control Unit (1RU)	Weight: 2 kg (4.5 lbs.) Size: 22.9 L x 26 W x 6.4 H cm (9"x 10.3"x2.5") with Power Supply and TraCLRi
Handheld Display Unit	Weight: 0.22 kg (0.5 lbs) Size: 14 L x 8.3 W x 3.5 H cm (5 <sup>1/2</sup> " x 3 <sup>1/4</sup> " x 1 <sup>3/8</sup> " )

# EXPLORER 7120

1.2 Meter Auto-Deploy, Drive-Away Antenna System



Antenna Characteristics	Ku Linear	
	Receive	Transmit
Frequency (GHz)	10.95 -12.75	13.75 -14.5
Antenna Gain (dBi ± 0.2)	41.6	43.1
VSWR	1.3:1	1.3:1
Cross Pol Isolation (dB) On-Axis	35	35
Cross Pol Isolation (dB) Off-Axis	27	28
Feed Port Isolation - Tx to Rx (dB)	35	80
Beamwidth (degrees)		
-3dB	1.5	1.2
-10dB	2.7	2.2
Antenna Noise Temperature (°K) at 20° Elevation	54°	
Radiation Pattern Compliance	FCC §25.209, ITU-R S.580-6	
Polarization	Linear Orthogonal Std Optional Co-pol	
Standard BUC Options	4W, 8W, 16W	



## Cobham Antenna Controller

Industry standard setting one-button auto-deploy operation with automatic satellite acquisition and cross-pol adjustment, integrated GPS, GLONASS, Compass, Level Sensors and user configurable satellite selection for primary and secondary satellites.



## Environmental

Wind Speed - Operational	72 km/h (45 mph)
- Survival (deployed)	105 km/h (55 mph)
- Survival (stowed)	129 km/h (80 mph)
Temperature - Operational	-30° to +52°C (-22° to 125°F)
- Survival	-40° to +60°C (-40° to 140°F)
Rain	<100 mm/hr
Humidity	0 to 100% (condensing)

## Integrated "TracLRI" GUI Feature:

The Live Remote Interface (LRI) is a web-based graphical user interface accessory for EXPLORER satellite antenna terminals. TracLRI communicates with any Cobham Antenna Controller Unit (ACU) and allows the user to easily configure and remotely monitor satellite auto-acquisition operations using a standard web browser. Available on a variety of devices such as PCs, tablets and smart phones.



## Electrical

RF	Rx and Tx: Type F (75-ohm) connectors
Interfacility Link	9.14m (30 ft) Dual RG6 Coax, 1 Control Cable
Motors	24VDC Servo w/ Optical Encoder, Constant Torque
Controller (1RU)	90 - 264 VAC, 50/60Hz Single Phase
Power Supply	300W standard; 1000W option available
Power Consumption	Motors Active – 250 Watts Motors Idle – 30 Watts
BUC Mounting	Feed Boom (maximum weight 7.3 kg / 16 lbs.)
Waveguide	90° WR75 Waveguide Rotary Joint @ Feed TX Input
Emergency Drive	Handcrank on Az & El; Knob on Pol

## About EXPLORER Products

Cobham SATCOM Land offers a diverse array of turn-key satellite terminals that fulfill critical communications needs and reduce system configuration requirements for end users. The solutions we provide offer a wide variety of data rates in multiple frequency bands including L, Ku, Ka, and X-bands. Systems are available as manual, or auto-deploy configuration, and are organized in drive-away, fly-away and common-the-move (COTM) families. When traditional communication technologies are unavailable or fail, our products provide high quality VoIP, RoIP, FAX, data, and multimedia communications that work efficiently across satellite links. We specialize in assisting partners with integrated end-to-end solutions for rapid deployment to support disaster recovery, continuity of operations and other mission critical applications.

For further information please contact:

Cobham SATCOM Land  
2100 N Alafaya Trail Suite 300  
Orlando, Florida 32826 USA  
Tel: +1-407-650-9054  
Fax: +1-407-650-9086

Subject to change without further notice.